Nano World Journal

https://doi.org/10.17756/nwj.2023-s3-063

Research Article

Open Access

Energy Efficient Resources Allocation on Multi Rat Cognitive Radio Network Using Nanotechnology

Sabeenian Royappan Savarimuthu[1*], Nandhini Thenmozhi Jaisankar[2] and Manjunathan Alagarsamy[3]

[1]Department of Electronics and Communication Engineering, Sona College of Technology, Salem, Tamil Nadu, India
[2]Department of Electronics and Communication, Sona College of Technology, Salem, Tamil Nadu, India
[3]Department of Electronics and Communication Engineering, K. Ramakrishnan College of Technology, Trichy, Tamil Nadu, India

[*]Correspondence to:
Sabeenian Royappan Savarimuthu
Department of Electronics and Communication Engineering,
Sona College of Technology,
Salem, Tamil Nadu, India.
E-mail: sabeenian@sonatech.ac.in

Received: July 28, 2023
Accepted: October 10, 2023
Published: October 12, 2023

Citation: Savarimuthu SR, Jaisankar NT, Alagarsamy M. 2023. Energy Efficient Resources Allocation on Multi Rat Cognitive Radio Network Using Nanotechnology. *NanoWorld J* 9(S3): S350-S359.

Copyright: © 2023 Savarimuthu et al. This is an Open Access article distributed under the terms of the Creative Commons Attribution 4.0 International License (CCBY) (http://creativecommons.org/licenses/by/4.0/) which permits commercial use, including reproduction, adaptation, and distribution of the article provided the original author and source are credited.

Published by United Scientific Group

Abstract

The common issue of user organization, allocation of resources, and base station (BS) implementation occurs when a network is heterogeneous (Het-Net) is helped by several radio-accessing technologies (Multi-RAT). Real-time user situations make it difficult to allocate resources in Het-Net optimally while guaranteeing that every user receives the smallest necessary information rate. Due to the current enormous development of wireless network systems and the exponential growth of data congestion, there is legitimate worry about the corresponding sharp rise in energy usage. In order to tackle these issues, the study here provides a brand-new method that combines an established and effective metaheuristic optimization approach. Consequently, the importance of energy-effective layout in multi-RAT systems is rising. Numerous radio-accessing technologies (RATs) have developed and are currently coexisting in order to serve the varied needs for the network's infrastructure and mobile user equipment (UE). These RATs operate with different network settings and allocations of resources. A promising technique to address the issue of spectrum scarcity is cognitive radio (CR) technology. System capacity may be increased via multi-radio accessing technologies (multi-RAT). In order to increase the efficiency of spectrum and network flexibility for subsequent wireless systems, multi-RAT integrated into a cognitive Radio Network (CRN) is a potential model. Considering the novel CRN concept used in this research, in which the principal users make up the principal user channels. Concentrate the study on the CR's Energy Effective Resources Allocation (EERA) challenge. The research recommends using the orthogonal frequency division multiple access with two-tier cross-over genetics algorithm-based searching approach (OFDMA-TTCGA) to discover a solution with the optimum processing power and bandwidth. The fundamental and crucial method employed by CR to locate unutilized airwaves is spectral sense. A spectrum detector employing the detection of energy has been suggested. Simulation outcomes demonstrate the stability and quicker convergence of the suggested approach. The effectiveness of energy use may be greatly improved with the suggestion. The results of simulations demonstrate that the suggested approaches can get performances close to the ideal solution with a great deal simpler structure and a greater efficiency of energy than a traditional spectral-efficiency-based method.

Keywords

Energy efficient resource allocation, Cognitive radio network, Multi radio access technology, Spectrum efficiency

Introduction

The need to reduce wireless systems' energy usage is growing both financially and ecologically as the use of smart wireless technology increases in favor and

mobile data traffic soars. So, for the upcoming generation of cellular networks, energy efficiency will be crucial [1]. Numerous initiatives have been taken to increase the network's energy effectiveness, including adaptable base station sleep regulation, power-efficient MIMO and beamforming, as well as planning of resources and allotment. Additionally, increasing the power efficiency of user devices is important since it extends a battery's longevity, which improves the user's experience. In an effort to improve the uplink's power utilization, a number of energy-efficient resource utilization algorithms are being developed [2]. Network service providers are confronting an important obstacle to increase the system's capability because demand for traffic in wireless networks continues to soar due to the explosive growth of terminals. Het-Net design has been suggested as a possible method to increase spectral effectiveness per unit area when advancements in spectral performance at the connection levels approaching its theoretical constraints using present approaches [3]. Het-Nets can be made up of various cell sizes and radio connectivity technology, including wireless local area networks, the third-generation partnerships project-long term growth, and microwaves exposure that is globally interoperable. Any one coverage area is served by a number of radio accessible technologies working cooperatively and complementarily in a sort of Het-Net termed as a multi-RAT Het-Net. A smartphone user in a network like Het-Net might be considered users of equipment using cognitive radio frequency through software defining radios to increase spectral efficacy [4].

There are now a number of stringent connectivity demands due to the emergence of the IoMT and ground-breaking usages for 5G. These specifications call for wireless connections to be flexible and responsive in order to meet the requirements of numerous usages. In particular, for e-health apps, health care systems must be able to anticipate and respond quickly to emergencies in order to lower the possibility of chronic illnesses and death rates [5]. Yet, the vast volume of produced data and the high latency demands of emergency situations continue to be important obstacles for e-health platforms. Study have been driven to take advantage of the growth of the 5G network towards dense Het-Nets by the need for extremely low latency as well as additional quality-of-service (QoS) criteria [6]. By enhancing the possibility of spatially reuse of resources, 5G Het-Nets are anticipated to improve users' QoS, enabling a variety of efficiency enhancements, and satisfy a variety of service needs [7]. A device or edges will be allowed to interact with the structure of the network by using radio frequencies that are available over many spectrum bands by using multi-RAT. As a result, edge devices with numerous connections will be capable of navigate the accessible systems using many RATs at once. To address this, creative and flexible channel selection strategies that take into account the QoS needs for e-health while retaining great efficiency of spectrum over various networks are required.

Since spectrum is an essential resource that ought to be distributed rather than squandered from the standpoint of sustainable interaction, cognitive radio technology performs an important part in enhancing the thermal efficiency of wireless networks. Investigators' interest in multi-RAT is currently back due to its ability to boost effectiveness. It has been demonstrated that a multi-radio accessibility network's efficiency may be enhanced by more efficient resource allocation. Investigations thus concentrate on the multi-radio access system, in which the information streaming are divided into several sub streams that transmit concurrently. Numerous issues still need to be handled, including how to cut back on energy usage. Femtocell technologies enhance cellular coverage within a structure by offering an excellent short-distance connection to the consumer's devices using a minima power and inexpensive short-term device—cellular telecoms BSs. Therefore, it is a viable method to lower wireless systems' consumption of energy [8]. Utilizing a mix of CR and collaborative techniques, the European ICT C2POWER study aims to investigate, establish, and implement energy-efficient solutions for multi-standard wireless mobile gadgets. A CR is a type that can modify its broadcasting qualities in reaction to changing environmental conditions, in accordance with Mitola's concept [9]. The majority of present CR work concentrates on spectrum perception, which might enhance spectrum utilization. But attention shouldn't be restricted to just one setting, like a spectrum. The energetic recognition component of CR is the focus of the C2POWER research. There is rising demand for using CR concepts to provide cost-effective, greener communication. The primary goal is to provide an architecture for dynamic power optimization built on energy aware CRNs that can meet required QoS for particular radio settings and usages [10]. The setting consciousness component of CR chooses how to change its operation as it reacts to the context. One node's choice can affect the behavior of each of the other nodes in the CR system as well as the amount of power they use on their own. Because of this, these kinds of decision-making procedures may be quite participatory.

The preparation, coordination, and resources optimization of future Het-Nets depend heavily on the right distribution of radio resources. It is primarily utilized to provide improved system performance, greater connectivity to the network, and lower energy usage. But controlling and assigning radio resources like frequency in the Het-Nets, power, spectrum remains a difficult task. One of the major problems in the developing Het-Nets is the multi-RAT attribution for edge devices (i.e., RATs-edge device relationships) and RATs' allocation of power. These two allocations of radio resources problems have been approached using a variety of approaches, including optimization concept, ranking-based approaches, and games theory [11]. Although the majority of these traditional allocating resources techniques often have a few limitations. They need a complete and current understanding of the dynamics of the network. Tragically, acquiring such data is not feasible since the wireless connection rapidly changes because the majority of networks in the real world are changing and vary over time. Additionally, the majority of these traditional allocations of resources techniques have low scaling, large cost of computation, and inconsistent convergence rates. Owing to the tremendous heterogeneity of future Het-Nets in terms of the basic QoS and RATs requirements of apps supported in addition to the phenomenal growth in the quantity and variety of emergent edge devices, these problems are further made worse in these systems. The adoption of current resource allocation strategies in prospective wireless Het-Nets is extremely

challenging, if not feasible, due to all of the aforementioned problems and difficulties [12]. Therefore, it is crucial to create alternate methods for allocating resources that can meet these obstacles and swiftly adjust to the various systems' dynamics.

On the assumption that the enhancement of the connection among the transmitting and receiving ends is exactly known, certain of the most recent study on multi-RAT Het-Net is established. Due to network variations, a lack of suggestions capability, and estimates of channels and quantization errors it could be challenging and costly to precisely predict simultaneous channel gains among transmitting and receiving devices in a complex network in practice [13]. Especially for a cognitive multi-RAT Het-Net, an erroneous channels allocation will lead to conflicts between primary users and supplemental users in addition to cognitive errors in the framework. Yet, the majority of prior research on multi-RAT networking has concentrated on users' connections and capacity in single-carrier platforms; energy-effective planning for multi-carrier systems of OFDMA networks has mostly been restricted to a single-RAT system. A multi-RAT wireless system, which makes it more difficult since it is multi-carrier and multi-RAT, has seen little development on an energy-efficient layout that takes both into account. The study examines how to allocate resources in an OFDMA network with two-tier crossover systems while using minimal energy. The recommended allocation of resources methods in this article are distinct from existing resources allocation techniques for OFDMA structures in that resource allocations (e.g., subcarriers and powers) is carried out across numerous RATs to maximize the system's power efficiency; existing energy efficiency techniques in the literature only take a single-RAT networks into consideration.

A hierarchical structure known as a Het-Net that is made possible by the collaboration of several overlap radio accessibility technology (multi-RAT), has been identified as an attractive option to handle the constantly increasing demand for traffic in high-speed wireless systems. A conventional Het-Net could be made up of a layer on the surface of a microcell and/or a macrocell that contains tiny cells like femtocells and picocells. In order to operate effectively and sustainably, each RAT in a Het-Net has its own radio capabilities incorporated into a collection of shared wireless connections. At this point on, the efficacy of each RAT as entirety, instead of just one RAT, is considered for allocating radio resources [14].

The contribution of the present study is:

- Multi-RAT CRN with spectrum detection has a system to maximize the effectiveness of energy.
- Various issues have been identified and the study suggests resolving it by using optimum allocation of power.
- The article proposes an OFDMA with two-tier crossover genomics method with orthogonal frequency division multiple accesses.
- Lastly, simulation outcomes are shown to demonstrate the suggested system's enhanced efficiency.

An SDN-based wireless system has the ability to combine several optically small cell wireless systems with, LiFi, WiFi, 5G, and other types of networking in a single network area, thus many different elements go into the distribution of information in this type of network. The primary problem in such a situation is the massive amount of power usage required by the resources to operate every aspect of the network topology in order to preserve both speed and QoS. An SDN-based wireless network's utilization of energy is examined, and a method is offered to successfully minimize the user's device energy usage without sacrificing these characteristics. Considering the on-going fluctuations in the quantity and kind of resources required at an individual's device, this process, however, becomes extremely difficult. There, the concept of reinforcement learning emerges to the initially because it considers the ultimate need, which is the total conserving of power in the allocation of resources, rather than just the short-term targets. The data were then displayed to determine how the strategy may be used to conserve energy while allocating resources. This approach is ineffective since it necessitates an entire network reconfiguration [15].

Sophisticated communication advancement in network growth is CR. Due to advancements in remote contacts, the bandwidth challenge has become more focused. CR technologies have evolved as an option to this problem by permitting people without licenses to operate on the approved bands. The overwhelming popularity of remotely presenting has put barriers in the way due to the limited amount of spectrum that is accessible. Among the primary techniques dependent on spectrum energy identification is required to find the unused spectra in cognitive radio. Utilizing the authorized spectrum for the supplementary purpose and not creating impedance to primary users has been the essential requirement for authorizing CRs. Spectrum identification enables smart users to differentiate among unrecognized radio frequency portions and exempts the principal users from interference in this manner. Depending on the Adapting Threshold Spectra Energy Detecting (ATSED) method, power identification-based spectrum detection has been recommended in this study. Whenever the disturbance is unpredictable and the main user is able to ignore the disruption stage, the effectiveness of spectral identification utilizing ATSED may be considerably enhanced. This study uses the MATLAB Simulink program to create a model of framework that depends on spectral energy detection. The results of simulations show that a rise in Signal to Noise Ratio (SNR) significantly enhances the likelihood of identification. Additionally, it is observed that once the bandwidth factor rises, the chance of identification drops. Due to its poor performance caused by noisy ambiguity and the value of the threshold setting, this strategy is ineffective [16].

Collaborative detecting and transmission in relay-assisted CRNs with constrained battery life depend on the effectiveness of energy (EE). The censorship-based relaying transmitting (CRT) is an energy-efficient cooperate transmitting approach that combines geographical diversity with filtering reporting in the cooperative procedure. The most effective supplementary relays (SRs) support additional transmission to increase the quality of communication in the process of transmission phase and hence increase supplementary trans-

mitting effectiveness. Particularly, supplementary relays (SRs) participate in collaborative sense with differentiated filtering to minimize energy usage. The research's initial stage was to generate generalized-form formulas for the CRT's detecting likelihood, reported likelihood, sensory power, and predicted performance. By jointly optimizing sensing time and power distribution for additional users under secondary likelihood of outages and sensory efficiency restrictions, study next examine an average energy efficiency-oriented maximization nonconvex issue. An effective cross-iteration technique with a simple structure is provided to acquire the suboptimal options, which is produced using the golden segmented searching technique, with the help of Jensen's inequality. At last, in-depth models are run to assess CRT's effectiveness. The outcomes highlight the advantages of the suggested cooperative technique in energy conservation for secondary transmission by demonstrating considerable increases in SUs efficiency of energy when compared to conventional noncooperative single cognitive systems for transmission. This approach is ineffective because it cannot distinguish between internal and exterior faults [17].

Networks slicing, which virtualizes equipment, radio, and energy resources as a network of logic while taking into consideration the needs of different uses, constitutes one of the cornerstones of the 5G framework. The distribution of resources in 5G RANs is connected with diverse issues owing to networking dynamics and the needs of the various apps, even though it ensures efficiency isolation across various slices. The distribution of electricity and radio signals to rate-based and resource-based consumers has been taken into account in this work. An approach for RAN sliced in 5G systems called EE-DRL-RA, or energy-efficient deeper reinforcement learning-assisted allocating resources, is suggested in the investigation. The basic concept of the proposed method is to employ an interactive educational framework which incorporates both deep learning (DL) and deep reinforcement learning (DRL) to decide how to distribute resources within the RAN. Study especially employs DRL for taking decisions on small-scale allocation of resources and DL for taking decisions on large-scale allocation of resources. Therefore, the DRL and supervised DL methodologies used are the stacked and bidirectional long-short-term memory (SBiLSTM) systems and the asynchronous benefit actor-critic (A3C). In addition, the investigation has the capacity to pinpoint the ideal power and resources blocks for rate-based customers by formulating the cost-effective allocating of power problem as a non-convex optimization problem and resolving it that way. The recommended approach stands out because it simultaneously transmits power and RBs, guarantees slices isolation, and does so with minimal computational and time cost. According to simulated findings, EE-DRL-RA outperforms an existing approach that is considered to be state-of-the-art in terms of converging velocity, difficulty of computation, effectiveness of energy use, the number of approved users, and the level of inter-slice isolates. This approach is ineffective since the system is slower and the training process takes longer [18].

The challenge of cost-conscious downstream sum-rate maximization through combined optimum RATs assigning and power distribution in next-generation Het-Nets is examined in this investigation. The study explores a hypothetical future Het-Net with many RATs and edge devices supporting multiple connections and the study defines the issue as a MINP issue. Due to the problem's high complexity and combinations nature, as well as the challenges in resolving it using conventional methods, the research shows a hierarchical multi-agent DRL-based framework, called DeepRAT, that can solve it efficiently and to learn the dynamics of networks. The RATsEDs assigning a phase, which employs a single-agent DQN method, and the energy allotment phase, which makes use of a multi-agent DDPG technique, are the two primary phases into which the issue is divided by the DeepRAT structure. Simulations are used in the investigation to demonstrate whether the various DRL agents connect in a useful way to comprehend the dynamics of the system and select the entire optimal plan of actions. The outcomes of the simulation further show that the proposed DeepRAT approach outperforms existing sophisticated heuristic techniques in terms of system utility. Last but not least, the study statistically demonstrates the DeepRAT model's capacity to flexibly and swiftly adjust to sudden changes in system dynamics, such as EDs' movement. This approach is ineffective because it typically reaches a local maximum rather than a global optimum [19].

The adoption of many coexisting radio-accessing technologies with various transmission and reception capabilities is anticipated for next-generation wireless networks. The radio spectrum front ends will be vulnerable to previously unheard-of adjacent-channel interference, which might impair the effectiveness of communication. This study offers a unique combined channel and power distribution approach that accounts for the receiver flaws caused by aliases in analog-to-digital converters and inadequate image frequency rejections. The objective is to minimize the number of allocated channels and the quantity of power transmitted while satisfying the rate demands of diverse connections in a multi-radio accessible technology scenario. The study provides an effective method to tackle the NP-hard issue by breaking it down into two smaller issues: channel allotment and energy allocation. After that, a two stages framework is used to iteratively resolve the decomposing issue. A method employing particle swarm optimization is developed in Phase I to find effective solutions to the channel's allotment subproblem. Considering the channel allotment solutions found in Phase I, Phase II resolves the energy allotment subproblem in the best possible way. The outcomes show how important receiver-characteristic knowledge is whenever constructing the allocation of resources systems and how excellent the recommended approach is at effectively resolving the entire issue. Due to its poor iteration rate of convergence and ease of falling into the local optimal in space with high dimensions, this strategy is ineffective [20].

The investigation puts forward the concept of power efficiency in the uplink with the possibility of multi-connectivity in multi-orbit non-terrestrial systems in order to enhance the highest possible throughput while consuming less power. UTs could be concurrently functioned by multiple satellites in this system, resulting in greater peak throughput. This idea also takes into account how users classify their services, which enables network sizing to be done in a way that satisfies user

demands for QoS. Although MC can boost throughput, doing so results in greater energy use at the user interface for uplink communications. In order to do this, a scheduling approach called EE-SAMC, or energy-effective service-aware multi-connectivity, is devised in this study. EE-SAMC makes use of the available radio frequencies and propagation data to effectively develop an adaptive resource utilization strategy that optimally routes traffic in order to reduce the consumption of energy at the UT while ensuring QoS is maximized. An optimization technique and a heuristic technique are used to tackle the non-convex combination issue that served as the basis for the creation of EE-SAMC. When compared to random allocation, round robin, and heuristic schedulers, EE-SAMC outperformed other schedulers in terms of efficiency of energy, latency, and throughput. Due to the difficulties with combinatorial optimization, this approach is ineffective [21].

Along with other innovations like the Internet of Things and machine learning, CR technology has gained recognition in recent years as the primary method for efficiently using spectrum. Without endangering cognitive users, it may utilize the unused spectrum resources as well as access the spectrum in a completely dynamical manner. Throughout this study, the investigators construct an effective deeper multi-user reinforcement learned system employing an integration of a Q-learning, DNN, and cooperating multi-agent systems as the basis for a CR accessing approach. The user selecting strategy is used for setting up the agent's activation sequence, and a frequency-selecting approach is used to choose the optimal channel for the bandwidth that is available. Together, these two stages make up the recommended approach. The investigated technique can enhance wireless interaction among all CR devices, as shown by the obtained findings and the feasible solution that is suggested. It functions effectively in terms of satisfaction with users and the number of networks used, and it can keep the channel's distribution approach in good condition. Due to the issue with the vanishing gradient, this approach is ineffective [22].

Methodology for Framework Design

The research takes into account a centralized cognition base station-coordinated multi-RAT CRN that includes several multiple primary users' network (PNet) and numerous secondary users' networks (SNets). Every SNet can be found in regions 1 and 2 of a PNet or in overlapped Regions 3 and 4, which are places in which more than two heterogeneity PNets exist together. Figure 1 depicts the allocating energy efficient resources for multi-RAT systems. The PNets might have additional wireless connectivity with varying ranges and operating at various spectrum frequencies, such as Wi-MAX, LTE, or Wi-Fi. A cognitive BS, numerous macro cells second-users (MSUs), numerous femtocells, and numerous femtocell secondary users (FSUs) are present in an overlapped area. Due to the adoption of OFDMA as the various access' technique by each of the two acknowledged 4G standards, OFDMA will be the predominant multiple accessing method for modern cellular networks. Excellent spectrum effectiveness and ease of use make OFDMA stand out. With this method, multiple



Figure 1: Allocating energy efficient resources for multi-RAT systems.

connections are made possible by giving various users different collections of orthogonal subcarriers. The advantage is that consumers that have high SNR can get subcarriers through adaptable allocation. Thus, the capacity of the system may be significantly boosted. This also goes by the name of multiple users' diversification.

Formulation of a problem

Resource allocation for femtocells in an energy-efficient way

The signals propagating scenario used in the present research is the COST Hata propagating losses concept. In feasible structures, there are typically two main kinds of detecting an erroneous false alarm, which takes place when the CR system incorrectly recognizes a frequency of a sub-channel as being not available whenever it is truly empty, as well as neglect identification, which happens whenever the CR system does not work to recognize the main the users signaling. The research indicates the likelihood of missed detection and false alarms.

$$\xi = \frac{\psi \log_2\left(1+\frac{k^2 q}{\delta^2}\right)}{q_b + q} \quad (1)$$

Wherein Ψ represents the bandwidth of the transmission, k and q are the channel gain and allocation of power, accordingly; q_b is the extra circuitry strength consumed by devices throughout propagation (such as digital to analog conversion devices as well as filters), that is not dependent on the information's transfer power; and δ^2 is an additive white Gaussian noise with a zero average and sections variability. The obvious equation (1) is to trade off transfer energy use and communication pace in order to transfer greater information with less energy. The femtocell's efficiency of energy (EE) in bits per joule is provided by:

$$\xi_{EE} = \frac{\sum_{i=1}^{n} R_i}{\sum_{i=1}^{n} E_{ci} + E_c} \quad (2)$$

Wherein Ec is the system's usage of energy and Ri is the femtocell reception.

Generally, the collection of functioning RATs and the subcarrier allocation for the provided RATs may be simultaneously optimized to attain the greatest energy efficiency. In most cases, the active RATs and the accompanying allocation of resources must be thoroughly researched in order to find the best option. Subsequently, find that turning RAT(s) off and on a regular basis isn't practicable because doing so requires time and money. In order to accomplish that, it seems more logical and practicable to choose an operational RAT on an extended time frame, i.e., depending on a median daily traffic profile found via multiple measurements. The study chooses a greater number of active RATs whenever the median traffic level is considerable; the study utilizes fewer functional RATs whenever the mean traffic gets comparatively low. Given that actual networks often have less than five prospective RATs, it is feasible to perform an offline comprehensive search to create a lookup table for choosing the best operational RATs. The study just assumes that Mac and Mid are supplied and concentrate on the allocation of resources for the specified operational RATs in order to keep things simple without sacrificing generalization. Simple integration of the presented methods into an off-line comprehensive search for the operational RAT choosing is possible.

Allocating resources efficiently for MSU

The ideal issue was examined as a highly difficult multifunctional nonlinear restricted optimization challenge. The study changes the maximization issue into an issue of minimization this way in order to streamline the theoretical evaluation.

$$Min\xi_{EE}\left(q_i, kR_{i,k}\right) = \frac{\sum_{i=1}^{i}\sum_{k=1}^{k} q_i, kE_{i,k} + E_c}{\sum_{i=1}^{i}\left(\sum_{k=1}^{k} q_i, k\log\left(1 + E_i, kX_{i,k}\right)\right)} \quad (3)$$

$$Max\left(q_i, kE_{i,k}\right) = \frac{\sum_{i=1}^{i}\sum_{k=1}^{k} q_i, k\log\left(1 + E_i, kX_{i,k}\right)}{\sum_{i=1}^{i}\left(\sum_{k=1}^{k} q_i, kE_{i,k} + E_c\right)} \quad (4)$$

The above equation states that research could accomplish the goals of the ideal issue by reducing energy use and increasing the data transfer rates.

Femtocell or MSU spectrum allotment method

Equation 5 could be used to express the signal-to-interference-plus-noise ratios (SINR) of MSU serviced by cognitively base station b via the i[th] sub-channel.

$$SINR^{k}{}_{n,b} = \frac{\chi_b \left|g_b^k\right| E_b}{\sum_{a\neq b}\sqrt{b_a}\left|g_a^k\right| E_a + V_b^2} \quad (5)$$

Wherein χ_b and $\sqrt{b_a}$ stand for the route losses of the cognitive BS that serves it and the cognitive BS that is next to it, accordingly; $g_b{}^k$ and $g_a{}^k$ stand for the path gains of the cognitive BS that is assisting it and the cognitive BS that is next to it, accordingly. V 2 is for the variability of the complicated circular symmetrical additive white Gaussian noise (AWGN) of the Cognition BS b. E_b and E_a stand for the transmitted signal's powers of the supplying Cognitively BS, b, and the nearby Cognition BS, a, accordingly. In the same manner, the SINR of the femtocell users' f active for the kth sub-channel may be shown as:

$$SINR^{k}{}_{n,b} = \frac{\left|g_b{}^k\right|^2 \overline{SNR_b}}{\sum_{a\neq b}\left|g_b{}^k\right|^2 \overline{SNR_a} + 1} \quad (6)$$

Proposed approach

It has been suggested to apply power detection-based spectral monitoring, which increases the efficiency of energy while increasing the efficiency of the spectrum instead of only lowering the possibility of false alarms. Establishing a radio context map and allocating resources to control network synchronization. Outcomes of the simulations demonstrate the suggested method's stability, quicker convergence, and FAP and MDP. The effectiveness of energy use may be greatly improved with the suggestion.

Energy efficiency with nanotechnology

Nanotechnology is technology that fabricates the molecules at the particular quantum mechanisms, that leads to measure a signal and it scaled by nanoscale. Nano technology is defined for the manipulation of matters with at least one dimension of size from 1 to 100 nanometers nm. This technology is used in the research categories that caused between the various range of thresholds. And with this nanotechnology, the transmission of power will be constructed at a higher data rate in radio networks. Power allocation can be measured through nano scaling to get optimal energy efficiency.

Functionality of chromosomes and fitness

A feasible approach is a single chromosome made up of (P + S) sub chromosomes. Energy-efficient allocation of resources aims to transfer greater amounts of information with less amount of transmitting energy. As a result, the research suggests the aggregate weighed fitness measure depicted follows.

$$f = \delta_1 f_{\min}{}^{P} + \delta_2 f_{\max}{}^{R} \quad (7)$$

Wherein f_{min} power and fmax rate are sub-fitness functional to reduce energy usage and increase the rate of data transfer, accordingly; δ_1 and δ_2 are the weights that are used to reduce energy usage and increase the transfer of data rates, accordingly.

Probability of initial population and selected regeneration

The two-stage crossovers GA search technique randomly generates the starting populace. So, it may be acquired by using

random values inside the range of the variables. The fitness rating of the following populations chooses the chromosome. Increasing chromosomal fitness scores increases the chance of chromosomes being selected. In the present investigation, chromosomes are chosen using a wheel of roulette selecting a strategy, in which every chromosome in the community is assigned a position in the wheel based on its fitness functionality. Consequently, as illustrated in equation 8, the study ought to estimate the chosen regenerating likelihood for every chromosome depending on the fitness value:

$$P_s = \frac{f(i)}{\sum_{k}^{N} f(k)} \quad (8)$$

Wherein N represents the population size and f(i) indicates the fitness function's determination of the i^{th} chromosomal value. P_s, a random value between 0 and 1, stands for the chosen regenerating probability of the i^{th} chromosomal. A shorter chromosome would be picked while all others would be discarded whenever a random number is contrasted to every chromosomal selecting probability. Consequently, an entirely novel population is created once more.

Operators with evolutionary processes

The evolving operations (crossover and mutation, for example) function with an unchanged probability in typical GAs. It is ineffective for many object fitness functions, though. In order to change both crossover and mutant probability in accordance with the function of fitness, the study applies an adaptive adjusting approach. The likelihood may be calculated as following:

$$\lambda_1 = \lambda_2 = 0.01\frac{f_{\max} - f_{avg}}{f_{\max} - f_{\min}}, if \ldots f_{\max} > f_{\min} \quad (9)$$

Wherein f_{max} and f_{min} stand for the highest and minimal fitness, subsequently, and f_{avg} stands for the median fitness score. accordingly. λ_1 and λ_2 reflect the number of modifications in the likelihood of crossover and mutation, accordingly.

A crossover is a significant procedure to locate the best option after population screening. The adaptable crossover procedure that the study suggests in this work comprises two tiers of crossover, referred to as one-tier crossover and two-tier crossover, accordingly. Considering the crossover likelihood determined by equation 9, two sets of chromosomes are chosen to accomplish a crossover in the one-tier crossover instance. With the exception of the inside of a sub chromosomal, the crossing site is selected at random from two- parent chromosomal. In order to broaden the identification area and quicken searching times, the two-tier crossover procedure is also required provided the sub-chromosome. Depending on two tier crossover likelihood, one chromosome decides whether to do a two-tier crossover. The two-tier crossovers broaden the range of searches in this manner to ensure that the chromosomal adheres to the limitations. The two-layer crossovers GA finding strategy increases both convergence speed and space for search using one-tier and two-tier crossover. Therefore, in the subsequent populace, steady chromosomal are looked for as excellent genes.

Evaluation of computation complexity

The research in the prior section indicates that the encoded data, determining fitness, and two-tier crossover procedures are all part of the suggested scheme's computational challenge. In this work, the study uses a binary encoding technique. This encoding approach has reduced the complexity of computation and processing time since the order of the genes is irrelevant. The suggested GA may acquire ((K + M) + P) chromosomal in the two-tier crossovers. Therefore, high population dimensions can be initialized for the investigation.

OFDMA two-tier cellular network

However, a new study has identified OFDMA systems as an attractive method for accommodating the greatest number of users in a way that is energy-efficient. This method divides the range of frequencies into a large number of subcarriers (smaller in size bands) that may be distributed among numerous users in an OFDMA network. Excellent spectral effectiveness and resistance to interference from multiple paths characterize OFDMA devices. Wireless technology like WiMAX and LTE-A, which provide international compatibility for microwave accessibility, are suitable for OFDMA [23]. The macrocell and femtocell utilize the same spectrum for operation. Each FemtoCell has a different cell-ID. Every piece of FemtoCell equipment used by users has the ability to detect interfering and submit the results to FAPS. In order to build FemtoCell groupings, FemtoCells are outfitted with global positioning system sensors that provide an exact approximation of their positions. FemotCells can only communicate with one another over air or backhaul. Separate clustered are formed from the FemtoCells. The goal of clustered is to separate the FemtoCell network's combined sub-channel and allocation of power challenges into more manageable sub-problems. One FemtoCell is chosen to serve as the leader of every cluster and is in charge of allocating sub-channels and energy. Clustered is easily accomplished by assembling FemtoCells that are nearby to one another. Additionally, every cluster has access to the whole collection of sub-channels, and no two FemtoCells can broadcast concurrently on the identical sub- channel inside a cluster [24].

As a result, there isn't any co-tier interfering inside the cluster. Regarding clusters sizes, numerous setups are possible. The worst-case scenario is to have an enormous clustering with all FemtoCells together. This arrangement has the advantage of removing co-tier interfering between FemtoCells. The proportion of every FemtoCell in the accessible spectrum, nevertheless, is quite little due to the enormous strain that performing allocations of resources places on the head. Another extreme is to allow a single femtocell to function on its own, which prevents clusters. Every FemtoCell in this scenario has access to the whole spectrum, and allocation of resources complication is at its simplest. But there is significant co-tier interference [25]. In order to address the growing need for ubiquitous wireless connectivity coverage and better efficien-

cy, FemtoCell has been employed as an alternative. A greater amount of functioning UE may be accommodated in a given region of the identical radio spectrum in FemtoCell systems because to the tiny cell density. As a result, region spectrum effectiveness has increased. Since the usual site survey and planning of networks procedures are no longer required, FemtoCells are very economical. Due to the near proximity of the receiver and the transmitter, FemtoCell's broadcast power may be reduced and its SINR can be improved [26].

In order to safeguard the capacity of the network, a combined sub-channel and allocation of power technique was used for the downstream deployment of an OFDMA mixing FemtoCells system. Iteratively allocated and optimized transmit power for BS and OFDM sub-channels is a feature of the method. Because OFDMA is a versatile technology, FemtoCells have utilized it as their air-interface technologies. The exclusivity channels allocation removes intracellular contamination. Exclusive channel allocation states that only one UE is ever allowed access to a sub-channel at any time. The coordinating OFDMA multicell network's combined power allotment and planning issues may be resolved using the iterative method [27].

Results and Discussion

MATLAB simulation was used to produce the findings shown in this section. The research takes into account a streamlined multi-RAT CRN with several OFDM-based main users and zero mutual interference between them. Additionally, it is anticipated that every secondary user will be spread in the overlapped zone with various PNets and have a highest power of 20 mW. The research makes the assumption that PNets have total bandwidths of 4, 10, 16, and 22 MHz. Figure 2 illustrates the data transfer rate of a femto-access-point under various SNR scenarios. Here, nanotechnology is a technique that has been used to improve energy efficiency and can also get most of power allocation while transmission of multiple users. And this transmission is to promote sustainable signaling.

Studies can see from figure 2 that the transmission rate originally increased with its SNR. However, the transmission rate also rises whenever the SNR reaches a particular level. That is, when the channel's quality grows, the quality of the communication also accomplishes, and as a result, the rate of transmission also increases. Additionally, it is evident that the femto-access-point with superior channel conditions has lower SNR to achieve a higher rate of transmission. The proposed system resource allocation energy efficiency is compared to other existing conventional approaches such as single-antenna jammer UAV, SAG-IoRT, and IHM-VD. The comparison of the energy efficiency approaches is represented in table 1 and its performance evaluation is depicted in figure 3. From figure 3, the study shows that the existing approaches including single-antenna jammer UAV, SAG-IoRT, and IHM-VD has less efficiency compared to proposed OFDMA-TTCGA approach.



Figure 2: Performance evaluation of transmission rate in terms of SNR.



Figure 3: Performance evaluation of allocating resource energy efficiency.

Table 1: Comparison of proposed system resource allocating energy efficiency with existing approaches.

Ref.	Technique	Energy efficiency		
		Number of users		
		4	6	8
[28]	Single-antenna jammer UAV	0.20	0.15	0.1
[29]	SAG-IoRT	0.15	0.20	0.24
[30]	IHM-VD	0.14	0.17	0.22

Conclusion

In the present analysis, traffic offloading was used to analyze the best user connections and allocation of resources in a system using multi-RAT. In order to pick the RAT and associate users most effectively while maximizing networking value, a unique method is suggested. User equipment normalizes utilities for every category and contract that provide services that follow fading features, according to the optimum RAT depending on the level of quality of the services. In overlapped regions where diverse personalized networks of users and multi-RATs exist together, the research developed an energy-effective allocation of resources technique known as OFDM which uses a two-tier GA. Due to its ability to

perform two-tier crossovers after 900 cycles and to choose favorable genes for the subsequent populace, the assessment findings demonstrated that this technique had greater convergent. The outcomes demonstrated the two-tier crossover genetic searching strategy's capacity to identify an ideal resource allotment strategy. The suggested method significantly surpasses its competitors in network utilitarian maximization in terms of fitness and operational reliability. Additionally, effective cell design in multi-RAT demonstrates that base stations are placed in both RATs in accordance with user equipment densities and each user's individual data speed need. In future, the investigation is required to find a conversion solution that needs less time and has a simpler computational structure.

Acknowledgements

None.

Conflict of Interest

None.

References

1. Wang T, Li P, Wang X, Wang Y, Guo T, et al. 2019. A comprehensive survey on mobile data offloading in heterogeneous network. *Wireless Netw* 25: 573-584. https://doi.org/10.1007/s11276-017-1576-0
2. Yu G, Jiang Y, Xu L, Li GY. 2015. Multi-objective energy-efficient resource allocation for multi-RAT heterogeneous networks. *IEEE J Sel Areas Commun* 33(10): 2118-2127. https://doi.org/10.1109/JSAC.2015.2435374
3. Peng M, Wang C, Li J, Xiang H, Lau V. 2015. Recent advances in underlay heterogeneous networks: interference control, resource allocation, and self-organization. *IEEE Commun Surv Tutor* 17(2): 700-729. https://doi.org/10.1109/COMST.2015.2416772
4. Chen J, Zhou Y, Kuo Y. 2016. Energy-efficiency resource allocation for cognitive heterogeneous networks with imperfect channel state information. *IET Commun* 10(11): 1312-1319. https://doi.org/10.1049/iet-com.2015.0741
5. Abdellatif AA, Al-Marridi AZ, Mohamed A, Erbad A, Chiasserini CF, et al. 2020. ssHealth: toward secure, blockchain-enabled healthcare systems. *IEEE Netw* 34(4): 312-319. https://doi.org/10.1109/MNET.011.1900553
6. Awad A, Mohamed A, Chiasserini CF, Elfouly T. 2017. Network association with dynamic pricing over D2D-enabled heterogeneous networks. In IEEE Wireless Communications and Networking Conference, San Francisco, CA, USA.
7. Xu Y, Gui G, Gacanin H, Adachi F. 2021. A survey on resource allocation for 5G heterogeneous networks: current research, future trends, and challenges. *IEEE Commun Surv Tutor* 23(2): 668-695. https://doi.org/10.1109/COMST.2021.3059896
8. Parimala A, Lokpriya S, Revathi R, Kaviyarasi I, Meena M. 2017. Energy-efficient resource allocation and spectrum sensing for heterogeneous cognitive radio network based on two-tier crossover genetic algorithm. *SIJ Trans Comput Netw Commun Eng* 5(2): 28-34.
9. Zhang Q, Moessner K. 2012. A Context Aware Architecture for Energy Efficient Cognitive Radio. In Rodriguez J, Tafazolli R, Verikoukis C (eds) Mobile Multimedia Communications. Lecture Notes of the Institute for Computer Sciences, Social Informatics and Telecommunications Engineering. Springer, Berlin, pp 452-462.
10. Ostovar A, Keshavarz H, Quan Z. 2021. Cognitive radio networks for green wireless communications: an overview. *Telecommun Syst* 76: 129-138. https://doi.org/10.1007/s11235-020-00703-8
11. Hussain F, Hassan SA, Hussain R, Hossain E. 2020. Machine learning for resource management in cellular and IoT networks: potentials, current solutions, and open challenges. *IEEE Commun Surv Tutor* 22(2): 1251-1275. https://doi.org/10.1109/COMST.2020.2964534
12. Luong NC, Hoang DT, Gong S, Niyato D, Wang P, et al. 2019. Applications of deep reinforcement learning in communications and networking: a survey. *IEEE Commun Surv Tutor* 21(4): 3133-3174. https://doi.org/10.1109/COMST.2019.2916583
13. Sim MS, Park J, Chae CB, Heath RW. 2016. Compressed channel feedback for correlated massive MIMO systems. *J Commun Netw* 18(1): 95-104. https://doi.org/10.1109/JCN.2016.000012
14. Carvalho GH, Woungang I, Anpalagan A, Hossain E. 2015. QoS-aware energy-efficient joint radio resource management in multi-RAT heterogeneous networks. *IEEE Trans Veh Technol* 65(8): 6343-6365. https://doi.org/10.1109/TVT.2015.2478852
15. Kumar V, Kumar R. 2020. Energy efficient resource allocation using reinforcement learning in SDN based wireless networks. In International Conference on Smart Electronics and Communication, Trichy, Tamil Nadu, India.
16. Sarala B, Devi SR, Sheela JJJ. 2020. Spectrum energy detection in cognitive radio networks based on a novel adaptive threshold energy detection method. *Comput Commun* 152: 1-7. https://doi.org/10.1016/j.comcom.2019.12.058
17. Feng L, Sun J, Sun H, Tang S. 2020. Censoring-based relay transmission for achieving energy efficiency in cognitive radio networks. *Wirel Commun Mob Comput* 2020: 5104605. https://doi.org/10.1155/2020/5104605
18. Azimi Y, Yousefi S, Kalbkhani H, Kunz T. 2021. Energy-efficient deep reinforcement learning assisted resource allocation for 5G-RAN slicing. *IEEE Trans Veh Technol* 71(1): 856-871. https://doi.org/10.1109/TVT.2021.3128513
19. Alwarafy A, Çiftler BS, Abdallah M, Hamdi M, Al-Dhahir N. 2022. Hierarchical multi-agent DRL-based framework for joint multi-RAT assignment and dynamic resource allocation in next-generation hetnets. *IEEE Trans Netw Sci Eng* 9(4): 2481-2494. https://doi.org/10.1109/TNSE.2022.3164648
20. Nabil A, Padaki AV, Abdel-Rahman MJ, ElNainay M, MacKenzie AB, et al. 2018. On optimal resource allocation in multi-RAT wireless networks with receiver characteristic awareness. *IEEE Trans Cogn Commun Netw* 5(1): 103-118. https://doi.org/10.1109/TCCN.2018.2878005
21. Dazhi MN, Al-Hraishawi H, Shankar B, Chatzinotas S, Ottersten B. 2023. Energy-efficient service-aware multi-connectivity scheduler for uplink multi-layer non-terrestrial networks. *IEEE Trans Green Commun Netw* 7(3): 1326-1341. https://doi.org/10.1109/TGCN.2023.3269283
22. Elhachmi J. 2022. Distributed reinforcement learning for dynamic spectrum allocation in cognitive radio-based internet of things. *IET Netw* 11(6): 207-220. https://doi.org/10.1049/ntw2.12051
23. Palit B. 2017. Cross layer design of schedulers for quality of service provisioning of multi-class traffic in wireless networks. Department of Computer Science, Indian Institute of Technology Kharagpur, India. (Doctoral Dissertation)
24. Soleimani B, Sabbaghian M. 2018. Cluster-based resource allocation and user association in mmWave femtocell networks. *IEEE Trans Commun* 68(3): 1746-1759. https://doi.org/10.1109/TCOMM.2018.2881464
25. Al-Omari M, Ramli AR, Sali A, Azmir RS. 2016. A femtocell cross-tier interference mitigation technique in OFDMA-LTE system: a cuckoo search based approach. *Indian J Sci Technol* 9(2): 1-12. https://doi.org/10.17485/ijst/2016/v9i2/80490
26. Fan C, Li B, Zhao C, Guo W, Liang YC. 2017. Learning-based spectrum sharing and spatial reuse in mm-wave ultradense networks. *IEEE Trans Veh Technol* 67(6): 4954-4968. https://doi.org/10.1109/TVT.2017.2750801

27. Khan AS, Abdullah J, Lenando H, Nazim JM. 2016. Green resource allocation for multiple OFDMA based networks: a survey. *J Electron Sci Technol* 14(2): 170-182.

28. Cai Y, Wei Z, Li R, Ng DWK, Yuan J. 2020. Joint trajectory and resource allocation design for energy-efficient secure UAV communication systems. *IEEE Trans Commun* 68(7): 4536-4553. https://doi.org/10.1109/TCOMM.2020.2982152

29. Li Z, Wang Y, Liu M, Sun R, Chen Y, et al. 2019. Energy efficient resource allocation for UAV-assisted space-air-ground Internet of remote things networks. *IEEE Access* 7: 145348-145362. https://doi.org/10.1109/ACCESS.2019.2945478

30. Li S, Ni Q, Sun Y, Min G, Al-Rubaye S. 2018. Energy-efficient resource allocation for industrial cyber-physical IoT systems in 5G era. *IEEE Trans Ind Inform* 14(6): 2618-2628. https://doi.org/10.1109/TII.2018.2799177